



value from this compact 400 and 250 Watt HID flood.

Color: Bronze

## **Technical Specifications**

## Listings

### **UL Listing:**

Suitable for wet locations. Suitable for ground mounting

## Electrical

#### Photocell:

480V Photocell Included. Photocell is only compatible with 480V.

#### Socket:

Glazed porcelain 4kv pulse rated with nickel plated screw shell and spring contacts.

#### **Ballast Volts:**

480 V

Starting/Operating Amps:

.75/.97A

# Construction

Housing:

Precision die cast aluminum.

## **Reflector:**

Weight: 33.2 lbs

High quality anodized aluminum.

Lens:

Tempered shock resistant glass.

## Lens Gasket:

Molded one-piece silicone in die cast retaining groove to remain in place during relamping.

Efficacy:

## Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

## EPA:

1.3.

## Other

Patents:

Pat. D547,478.

Project:		Туре:	
Prepared By:		Date:	
Lamp Info		Ballast Info	
Туре:	ED18	Туре:	CWA-HPF 480V
Watts:	400W	120V:	N/A
Shape/Size:	N/A	208V:	N/A
Base:	N/A	240V:	N/A
ANSI:	N/A	277V:	N/A
Hours:	24,000	Input Watts:	460W
Lamp Lumens:	50,000	Efficiency:	87%

## **Country of Origin:**

109 LPW

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

#### **Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

## Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

## **Trade Agreements Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.


#### **GSA Schedule:**

Suitable in accordance with FAR Subpart 25.4.

# FZS400SF/480/PCS4



# Dimensions



## Features

Optional glare hood, wire guard or polycarbonate shield

Reflector designed for precise beam control

Stainless steel screws included

Long life lamp included

Supplied with 3' of STW cord

Rugged trunnion or slipfitter mounting

New 2" Integra hood to reduce light trespass and glare