GL200PG





Color: Clear

Technical Specifications

Listings

UL Listing:

Suitable for wet locations when used with Vaporproof fixtures. Suitable for dry, damp or wet locations when used as replacement globes for listed fixtures. Fixtures must be installed with lamp base up when outdoors.

Construction

Polycarbonate Globe:

Clear thermal shock resistant polycarbonate standard.

4 15/16" 12.5 cm

Perma Globes:

Dimensions

Impact resistant UV stabilized polycarbonate.

Electrical

Maximum Wattage:

100 watts

Other

Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

Type:

Date:

Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

Features

Project:

Prepared By:

Unbreakable polycarbonate globe in two sizes and six colors

Industry standard 3 5/32" or 4 5/32" threads

Colors available for signaling or decorative applications



8 1/4" 21 Cm