



15" round die cast aluminum housing with vandalproof refractor for optimum parking garage light distribution. 150 or 175 w vertical mount Metal Halide or 100,000 hour Induction. Lamp supplied.

Color: N/A

Weight: 20.5 lbs

**Project:**

**Type:**

**Prepared By:**

**Date:**

### Lamp Info

Type: ED17  
 Watts: 150W  
 Shape/Size: N/A  
 Base: N/A  
 ANSI: N/A  
 Hours: 15,000  
 Lamp Lumens: 14,000  
 Efficacy: 74 LPW

### Ballast Info

Type: HX-HPF QT  
 120V: 1.4/1.7A  
 208V: .8/1.0A  
 240V: .7/.8A  
 277V: .6/.7A  
 Input Watts: 190W  
 Efficiency: 79%

## Technical Specifications

### Listings

#### UL Listing:

Suitable for wet locations. Fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from ballast.

### Construction

#### Mounting:

Ceiling mount only. Not suitable for pendant mounting.

#### Housing:

Cast aluminum housing with 1/2 inch threaded NPS conduit access on 2 sides at 180° and the top of the housing.

#### Housings:

Die cast aluminum with powder coat bronze or white finish.

#### Screws:

Tamperproof center pin Torx-head and slotted Phillips head stainless steel screws provided. Be sure to order your Torx screwdriver (Catalog # VANDRIVER).

### Reflectors / Backplate:

Heavy gauge cold rolled steel with high reflectance baked white enamel.

### Fluorescent Ballast Starting Temperatures:

Electronic QT 0°F/-18°C NPF 120V 32°F / 0°C.

### Electrical

#### Sockets:

HPS & MH Medium base 4kv Pulse Rated Glazed porcelain CFL Plug-in type, thermoplastic.

#### HID Quartz restrrike:

Add suffix "/QR" to Van3 (50w restrrike) or Van5 (100w restrrike) for HOT restrrike. Provides immediate illumination in case of momentary power failure.

#### Pulse Start:

Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency.

### Optical

#### Refractor:

Injection molded polycarbonate, designed for maximum structural strength.

### Other

#### Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

#### Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

#### Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

#### GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

## Features

- Vertical lamp for better light disbursement and heat dissipation
- Both Vandal proof Center Pin Torx and slotted Phillips head screws supplied
- Tough polycarbonate refractors and Die cast aluminum housings
- Philips QL induction system with 100,000 hours available. Consult factory