VBR100PW-B/F13





Die cast aluminum construction with sturdy wall mounting bracket. Medium base socket and a variety of globes. Lamp supplied.

Color: White Weight: 2.3 lbs

| Project: | Туре: |
|--------------|-------|
| Prepared By: | Date: |

| Lamp Info | | Ballast Info | | |
|--------------|----------|--------------|----------|--|
| Type: | 13W Quad | Type: | NPF 120V | |
| Watts: | 13W | 120V: | 0.35A | |
| Shape/Size: | N/A | 208V: | N/A | |
| Base: | N/A | 240V: | N/A | |
| ANSI: | N/A | 277V: | N/A | |
| Hours: | 10,000 | Input Watts: | 17W | |
| Lamp Lumens: | 825 | Efficiency: | 76% | |
| Efficacy: | 49 LPW | | | |
| | | | | |

Technical Specifications

Listings

UL Listing:

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90°C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

Electrical

Wattage:

See catalog number chart for maximum wattage with clear glass, colored glass and Permaglobes.

Socket:

Premium porcelain with 150°C 8" leads attached. Fastened with 2 stainless steel screws.

Construction

Globes:

Supplied with clear heat resistant glass globes unless otherwise stated. Colored and white glass globes available. Unbreakable RAB Permaglobes available in clear and in color.

Optional Reflectors:

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See RV series.

Globe:

Supplied with white flat bottom prismatic polycarbonate globe. Not for use with diecast or wire guard.

Optional Guard:

Order flat bottom guard separately. CAT# GD100BAR.

Ballast Minimum Starting Temperature:

32°F.

Optical

F13:

Compact Fluorescent 13W.

Other

Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

Features

Set screw keeps guard securely in place

All stainless steel hardware

Close-up plugs allow Phillips or slotted screwdrivers for easy installation

High temperature silicone internal gaskets

Premium porcelain socket with 150C 8" long leads attached