WP2CF42W/E1/PC





Color: White

Technical Specifications

Electrical

Emergency Battery Backup:

Bodine "Coldpak" will operate the CFL lamp for 90 minutes if power fails. Rated -20°C to 55°C. Battery is a maintenance free NiCad with 7 - 10 year life. Wired for 120V.

Photocell:

120V Button Photocell Included. Photocell is only compatible with 120V.

Listings

UL Listing:

Suitable for wet locations. HID fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from ballast.

Construction

Housing:

Die cast aluminum, 1/2" NPS tapped holes top, both sides and back for conduit or photocontrol. Hinged refractor frame. Continuous silicone rubber gasket.

Reflector:

Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

Cutoff Lens:

Tempered glass.

Finish:

Weight: 12.3 lbs

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

Optical Refractor:

Prismatic optics designed to minimize glare and throw light down and out. Heat resistant borosilicate glass.

Other

Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

Project: Prepared By:		Type: Date:		
				Lamp Info
Туре:	42W Triple	Туре:	Elec HPF QT	
Watts:	42W	120V:	0.38A	
Shape/Size:	N/A	208V:	N/A	
Base:	N/A	240V:	N/A	
ANSI:	N/A	277V:	N/A	
Hours:	10,000	Input Watts:	46W	
Lamp Lumens:	3,200	Efficiency:	91%	
Efficacy:	70 LPW			

Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).


Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

WP2CF42W/E1/PC



Features

Emergency battery backup meets NEC requirement

Test button for required maintenance checks

Indicator light illuminates when charging

Maintenance free NiCad battery has 7-10 year life

Silicone gasket remains in place during relamping

Top, side and back conduit openings

Long life lamp included

