



Fully shielded, Full Cutoff wallpack. Full Cutoff optics with flat tempered glass lens. EZ mount knockouts for easy wiring. Lamp supplied.

Color: Bronze Weight: 17.2 lbs

Project:	Туре:
Prepared By:	Date:

Watts:         32W         120V:         0.31A           Shape/Size:         N/A         208V:         N/A           Base:         N/A         240V:         N/A           ANSI:         N/A         277V:         N/A           Hours:         12,000         Input Watts:         32W	Lamp Info		Ballast Info	
Shape/Size:         N/A         208V:         N/A           Base:         N/A         240V:         N/A           ANSI:         N/A         277V:         N/A           Hours:         12,000         Input Watts:         32W	Type:	32w Triple	Type:	Elec HPF QT
Base:         N/A         240V:         N/A           ANSI:         N/A         277V:         N/A           Hours:         12,000         Input Watts:         32W	Watts:	32W	120V:	0.31A
ANSI: N/A 277V: N/A Hours: 12,000 Input Watts: 32W	Shape/Size:	N/A	208V:	N/A
Hours: 12,000 Input Watts: 32W	Base:	N/A	240V:	N/A
•	ANSI:	N/A	277V:	N/A
1 1 2 400	Hours:	12,000	Input Watts:	32W
Lamp Lumens: 2,400	Lamp Lumens:	2,400		
Efficacy: 75 LPW	Efficacy:	75 LPW		

# **Technical Specifications**

### **Electrical**

# Photocell:

120V Button Photocell Included. Photocell is only compatible with 120V.

### Listings

### **UL Listing:**

Suitable for wet locations. HID fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from ballast.

# Dark Sky Approved:

The International Dark Sky Association has approved this product as a full cutoff, fully shielded luminaire.

# Construction

## Housing:

Die cast aluminum, 1/2" NPS tapped holes top, both sides and back for conduit or photocontrol. Hinged refractor frame. Continuous silicone rubber gasket.

### Reflector:

Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

## **Cutoff Lens:**

Tempered glass.

#### Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

### For use on LEED Buildings:

IDA Dark Sky Approval means that this fixture can be used to achieve LEED Credits for Light Pollution Reduction.

# Optical

## Refractor:

Prismatic optics designed to minimize glare and throw light down and out. Heat resistant borosilicate glass.

# Other

## **Country of Origin:**

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

## **Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act

### Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).


## **Trade Agreements Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

## GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

### **Dimensions**



### **Features**

Tempered Glass Lens

Drilling template for easy box mounting

Silicone gasket remains in place during relamping

Top, side and back conduit openings

Full cutoff glare shield for friendly lighting

Long life lamp included