

<b>Project:</b>	<b>Type:</b>	<b>Prepared By:</b>	<b>Date:</b>
-----------------	--------------	---------------------	--------------



**Features and Benefits**

Technical Specifications		
<b>Performance</b>	<b>Dimmable:</b>	<b>Endcap Material:</b>
<b>Product Type:</b> A-Line	Yes	Polycarbonate
<b>Input Wattage:</b> 8.5W	<b>Compliance</b>	<b>Enclosure Material:</b> Plastic
<b>Lumens (Nominal):</b> 800lm	<b>UL Listed:</b> Suitable for damp locations	<b>Beam Angle:</b> 230°
<b>Efficacy:</b> 94.1 lm/W	<b>Enclosed Fixtures:</b> Suitable for use in enclosed fixtures	<b>Electrical</b>
<b>Color Accuracy (CRI):</b> >90 CRI	<b>LED Characteristics</b>	<b>THD:</b> 58%
<b>L70 Lifespan:</b> 15,000-Hour LED lifespan based on IES LM-70 results	<b>Color Temperature:</b> 2200K/3000K	<b>Power Factor:</b> 0.7
	<b>Construction</b>	
	<b>Bulb Shape:</b> A19	
	<b>Base Type:</b> E26	

**Technical Specifications (continued)**

**Electrical**

**Operating Temperature:**

-20°C - 45°C

**Input Voltage:**

120V

**Operating Frequency:**

60 Hz

**Other**

**Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

**Wattage Equivalency:**

60W Incandescent

**Case and Pallet Dimensions**

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	9.8	7.4	9.8
PALLET	1500	48	40	22.72

**Dimension**

