

Project: Type: Prepared By: Date:

×

UPC: 01.92552E+11







#### **Features and Benefits**

Replacement for High output incandescent or Metal Halide and High Pressure Sodium HID Lamps

Commercial Grade

Large metal heatsink for optimal heat dissipation

In HID retrofit applications - Integral Driver enables lamp to be wired directly to line voltage. Must bypass ballast

Rated for use in enclosed and open fixtures in dry or damp locations

Ideal for post top, bollards, and outdoor corridor lighting

Environmentally friendly, no mercury used

UL Listed, ENERGY STAR Compliant

Non-Dimmable

Universal Voltage 120 through 277V

50,000 hour Lifespan

5 Year No Compromise Warranty

# **Technical Specifications**

Performance

**Product Type:** 

A-Line

Input Wattage:

23W

**Typical Lumen Output:** 

2550lm **Efficacy:** 

110.9 lm/W

CRI:

>80

L70 Lifespan:

25,000-Hour LED lifespan based on IES LM-70 results

Dimmable:

Yes

Compliance

**UL Listed:** 

Suitable for damp locations

**Enclosed Fixtures:** 

Suitable for use in enclosed fixtures

**DLC Model Number:** 

A10075(A21-23-E26-830-DIM 120V)

**LED Characteristics** 

**Color Temperature:** 

3000K

Construction

**Bulb Shape:** 

A21

Base Type:

E26

**Enclosure Material:** 

Die Cast Aluminum

Beam Angle:

230°

Electrical

Power Factor:

>0.9

**Operating Temperature:** 

-20°C - 40°C



# **Technical Specifications (continued)**

**Electrical** 

Input Voltage:

120V

**Operating Frequency:** 

60 Hz

Other

# Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="mailto:rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-

### Wattage Equivalency:

150W Incandescent / Metal Halide or High Pressure Sodium

#### **Case and Pallet Dimensions**

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	12.7559	9.56693	5.9
PALLET	0	0	0	0