# ALED4T125SFN/PCS2





Specification grade area lights available with IES Type IV distribution. Suited for mounting on the sides of buildings and walls, and for illuminating the perimeter of parking areas. Patent pending management system. 5 Year Warranty.

Color: Bronze Weight: 32.0 lbs

| Project:     | Туре: |
|--------------|-------|
| Prepared By: | Date: |

| Driver Info  |                  | LED Info        |        |  |
|--------------|------------------|-----------------|--------|--|
| Type:        | Constant Current | Watts:          | 125W   |  |
| 120V:        | N/A              | Color Temp:     | 4000K  |  |
| 208V:        | 0.70A            | Color Accuracy: | 82 CRI |  |
| 240V:        | 0.61A            | L70 Lifespan:   | 100000 |  |
| 277V:        | 0.52A            | Lumens:         | 10,952 |  |
| Input Watts: | 137W             | Efficacy:       | 80 LPW |  |
| Efficiency:  | 91%              |                 |        |  |

## **Technical Specifications**

#### **Electrical**

#### Photocell:

277V Swivel Photocell Included. Photocell is compatible with 208V-277V.

#### Drivers:

Two Drivers, Constant Current, Class 2, 1750mA, 100-277V, 50/60Hz, 1.1A, Power Factor 99%

#### THD:

5.4% at 120V, 15.5% at 277V

## Surge Protection:

4kV

#### Listings

# UL Listing:

Suitable for wet locations.

### IESNA LM-79 & LM-80 Testing:

RAB LED luminaries have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80, and have been received the Department of Energy "Lighting Facts" label.

### **LED Characteristics**

## Lifespan:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

#### LEDs:

Multi-chip, high-output, long-life LEDs

### **Color Stability:**

LED color temperature is warrantied to shift no more than 200K in CCT over a 5 year period.

### **Color Uniformity:**

RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2011.

#### Construction

### **IES Classification:**

The Type IV distribution (also known as a Forward Throw) is especially suited for mounting on the sides of buildings and walls, and for illuminating the perimeter of parking areas. It produces a semiCircular distribution with essentially the same candlepower at lateral angles from 90° to 270°.

#### **Effective Projected Area:**

EPA = 2.2

#### **Maximum Ambient Temperature:**

Suitable for use in 40°C (104°F) ambient temperatures

### **Cold Weather Starting:**

The minimum starting temperature is -40°C/-40°F

## Thermal Management:

Superior thermal management with external Air-Flow fins.

#### Housing:

Die-cast aluminum housing, lens frame and mounting arm.

### Mounting:

Heavy-duty mounting arm with "O" ring seal & stainless steel screws

### Reflector:

Specular vacuum-metallized polycarbonate

#### Gaskets:

High-temperature silicone gaskets

#### IP Rating:

Ingress Protection rating of IP66 for dust and water.

#### Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

#### Green Technology:

Mercury and UV free. RoHS compliant components. Polyester powder coat finish formulated without the use of VOC or toxic heavy metals.

## For use on LEED Buildings:

IDA Dark Sky Approval means that this fixture can be used to achieve LEED Credits for Light Pollution Reduction.

## Optical

#### Replacement:

The ALED125 replaces 320W Metal Halide Area Lights.

#### **BUG Rating:**

B1 U0 G2

## Other

# California Title 24:

ALED4T125SF/PCS2 with the swivel photocell (277V) option complies with 2013 California Title 24 building and electrical codes as a commercial outdoor polemounted fixture > 75 Watts at mounting heights greater than 24 feet.



# **Technical Specifications (continued)**

## Other

#### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish.

## **Country of Origin:**

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

#### **Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

## Recovery Act (ARRA) Compliant:


This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

#### **Trade Agreements Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

#### **GSA Schedule:**

Suitable in accordance with FAR Subpart 25.4.



#### **Features**

66% energy cost savings vs. HID

100,000-hour LED lifespan

Type IV distribution

5-year warranty

| Family | Distribution                                  | Watts                                                                          | Mount                                | Color Temp                                                               | Finish                                      | Voltage                                            | Photocell                                                                                                                                                             | Dimming                                  | Bi-Level                                |
|--------|-----------------------------------------------|--------------------------------------------------------------------------------|--------------------------------------|--------------------------------------------------------------------------|---------------------------------------------|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|-----------------------------------------|
| ALED   |                                               |                                                                                |                                      |                                                                          |                                             |                                                    |                                                                                                                                                                       |                                          |                                         |
|        | 2T = Type II<br>3T = Type III<br>4T = Type IV | 360 = 360W<br>260 = 260W<br>150 = 150W<br>125 = 125W<br>105 = 105W<br>78 = 78W | Blank =<br>Arm<br>SF =<br>Slipfitter | Blank = 5000K<br>(Cool)<br>Y = 3000K<br>(Warm)<br>N = 4000K<br>(Neutral) | Blank =<br>Bronze<br>W = White<br>RG = Gray | Blank = 120-277V<br>/480 = 480V (Only 360W & 260W) | Blank = No Photocell /PC = 120V Button /PC2 = 277V Button /PCS = 120V Swivel /PCS2 = 277V Swivel /PCT = 120-277V Twistlock /PCS4 = 480V Swivel /PCT4 = 480V Twistlock | Blank = No<br>Dimming<br>/D10 = Dimmable | Blank = No Bi<br>Level<br>/BL = Bi-Leve |