## BR30-8.5-840-DIM ECO 6PK

Project:	Туре:	Prepared By:	Date:
<b>UUUUUUUUUUUUU</b>	UPC: 0192552005555         EFEE	lamps Constructed from Rated for use in er Frosted lens produ Longer lifespan co and maintenance ENERGY STAR Con Dimmable with co	
Technical Specificati	ons		
Performance	Dimmable:	В	ase Type:
Product Type:	Yes	E	26

Product Type:	Yes	E26
Reflector	Compliance	Endcap Material:
Input Wattage:	UL Listed:	Aluminum
8.5W	Suitable for damp locations	Enclosure Material:
Typical Lumen Output:	Enclosed Fixtures:	Plastic
650lm	Suitable for use in enclosed fixtures	Optical
Efficacy:	DLC Model Number:	Beam Angle:
76.5 lm/W	A10066(BR30-8.5-840-DIM ECO)	120°
CRI:	LED Characteristics	Electrical
80	Color Temperature:	Power Factor:
L70 Lifespan:	4000K	0.7
15,000-Hour LED lifespan based on IES LM-70 results	Construction	
	Bulb Shape:	
	BR30	

RAB

## BR30-8.5-840-DIM ECO 6PK

## **Technical Specifications (continued)** Electrical **Operating Frequency:** Wattage Equivalency: 60 Hz 65W Halogen **Operating Temperature:** Other -20°C - 45°C Input Voltage: Warranty (Years): 120V RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

## Case and Pallet Dimensions QTY LENGTH (in) WIDTH (in) HEIGHT (in) CASE 24 19.9 14.6 19.9 PALLET 720 45.47 41.34 41.34

