# **BR40-12-830-DIM**

Project:	Туре:	Prepared By:	Date:
		Reflector lan Constructed Rated for us locations Frosted lens Longer lifes replacemen ENERGY STA	<b>Features and Benefits</b> ient replacement for incandescent and halogen mps I from durable plastic which lowers risk of breakage is in enclosed and open fixtures in dry or damp is produces smooth diffuse light pan compared to legacy equivalents minimizes t and maintenance costs AR Compliant with common dimmer types (check compatibility list)
Technical Specifica Performance	tions Dimmable:		Base Type:
Product Type:	Yes, down to 10%	6	E26
Reflector	L70 Lifespan:		Beam Angle:
nput Wattage:	25,000-Hour LED results	lifespan based on IES LM-70	110° Electrical
Lumens (Nominal):	Construction	l	Power Factor:
1100	Bulb Shape:		>0.7
Efficacy:	BR40		Input Voltage:
92 lm/W	Enclosure Mat	terial:	1201

92 lm/W

**Color Accuracy:** 

80

**Color Temperature:** 

3000K

Enclosure Material: Plastic **Housing Finish:** White Lens Finish: Frosted

120V **Operating Frequency:** 60 Hz

RAB

# Technical Specifications (continued)

#### **Electrical**

Operating	Temperature:
-----------	--------------

-20°C-45°C

Other

Equivalency:

85

**Technology EQ:** 

Incandescent

## Warranty (Years):

3 years

Compliance	
UL Listed:	
Yes	
Environment/Fixture Rating:	
Damp / Enclosed	
Energy Star ID:	
2356243	

#### Rohs:

Mercury and UV free. RoHS-compliant components.

Complies with Part 15 of the FCC Rules

### Model Number:

R10051(BR40-12-830-DIM)

#### Dimension **Minimum Compartment Size** Length x Width x Height [in] Lamp Quantity 4 15/16″ 125mm 15.83 x 10.71 x 7.24 1 **Case and Pallet Dimensions** QTY LENGTH (in) WIDTH (in) HEIGHT (in) 6 5/16″ 160mm CASE 6 0 0 0 PALLET 360 0 0 0