



| | |
|---------------------|--------------|
| Project: | Type: |
| Prepared By: | Date: |

Technical Specifications

Construction

Lens:

Tempered, soda lime glass, 3mm thick (nominal 1/8"); can be sand blasted for additional diffusion

Color:

Fade-resistant color is molded into the glass

Frame and L Rails:

Die-formed 0.40 aluminum with powder-coated finish

LED Characteristics

Light Loss Factor:

0.04

Other

Color Filter:

Ruby red

Compatibility:

FFLED 18W in bronze finish

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Features

- Simple to install or swap colors (4 screws for easy mounting)
- Durable, tempered glass withstands outdoor use
- Aluminum frame construction with RAB's durable, polyester power-coat finish

Ordering Matrix

| Family | Fixture | Filter Color | Frame Finish |
|--------|--|--|---------------------------------------|
| CF | FF18 | R | A |
| | FX300 = FXLED300 FXLED200 FX150 = FXLED150 FXLED125 FXLED105 FXLED78 EZ78 = EZLED78 CANVAS78 FF120 = FFLED120 FF80 = FFLED80 FFLED52 FFLED39 FFLED26 FF18 = FFLED18 | B = Blue LB = Light Blue G = Green MG = Medium Green LG = Light Green R = Ruby Red MR = Cherry Red MA = Medium Amber LA = Light Amber PP = Pale Purple Y = Yellow | A = Bronze W = White |