CF-FF80-B-W





| Project: | Туре: |
|--------------|-------|
| Prepared By: | Date: |

Technical Specifications

| Construction | LED Characteristics | Buy American Act Compliance: | |
|--|--|--|--|
| Lens: | Light Loss Factor: | RAB values USA manufacturing! Upon request, RAB | |
| Tempered, soda lime glass, 3mm thick (nominal 1/8"); | 0.05 | may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant. | |
| can be sand blasted for additional diffusion | Other | | |
| Color: | Color Filter: | | |
| Fade-resistant color is molded into the glass | Blue | | |
| Frame and L Rails: | Compatibility: | | |
| Die-formed 0.40 aluminum with powder-coated finish | FFLED 26W, 39W, 52W, 80W in white finish | | |

Features

Simple to install or swap colors (4 screws for easy mounting)

Durable, tempered glass withstands outdoor use

Aluminum frame construction with RAB's durable, polyester power-coat finish

Ordering Matrix

| Family | Fixture | Filter Color | Frame Finish |
|--------|--|---|-------------------------|
| CF | FF80 | В | W |
| | FX300 = FXLED300 FXLED200 FX150 = FXLED150 FXLED125 FXLED105 FXLED78 EZ78 = EZLED78 CANVAS78 FF120 = FFLED120 FF80 = FFLED80 FFLED52 FFLED39 FFLED26 FF18 = FFLED18 | B = Blue LB = Light Blue G = Green MG = Medium Green LG = Light Green R = Ruby Red MR = Cherry Red MA = Medium Amber LA = Light Amber PP = Pale Purple Y = Yellow | A = Bronze W = White |

Need help? Tech help line: (888) RAB-1000 Email: sales@rabweb.com Website: www.rabweb.com

Copyright © 2014 RAB Lighting Inc. All Rights Reserved Note: Specifications are subject to change at any time without notice