



Project:	Type:
Prepared By:	Date:

Technical Specifications

Construction

Lens:

Tempered, soda lime glass, 3mm thick (nominal 1/8"); can be sand blasted for additional diffusion

Color:

Fade-resistant color is molded into the glass

Frame and L Rails:

Die-formed 0.40 aluminum with powder-coated finish

LED Characteristics

Light Loss Factor:

0.08

Other

Color Filter:

Medium green

Compatibility:

FXLED 200W, 300W in white finish

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Features

- Simple to install or swap colors (4 screws for easy mounting)
- Durable, tempered glass withstands outdoor use
- Aluminum frame construction with RAB's durable, polyester power-coat finish

Ordering Matrix

Family	Fixture	Filter Color	Frame Finish
CF	FX300	MG	W
	FX300 = FXLED300 FXLED200 FX150 = FXLED150 FXLED125 FXLED105 FXLED78 EZ78 = EZLED78 CANVAS78 FF120 = FFLED120 FF80 = FFLED80 FFLED52 FFLED39 FFLED26 FF18 = FFLED18	B = Blue LB = Light Blue G = Green MG = Medium Green LG = Light Green R = Ruby Red MR = Cherry Red MA = Medium Amber LA = Light Amber PP = Pale Purple Y = Yellow	A = Bronze W = White