



Compact, tough and good looking cast aluminum housing with hinged framed glass lens. Integra Hood glare shield and stainless steel clip. Lamp supplied.

Color: Bronze Weight: 9.9 lbs

Project:	Туре:
Prepared By:	Date:

_amp Info		Ballast Info	
Гуре:	32w Triple	Type:	Elec HPF QT
Vatts:	32W	120V:	N/A
Shape/Size:	N/A	208V:	N/A
lase:	N/A	240V:	N/A
NSI:	N/A	277V:	0.13A
ours:	12,000	Input Watts:	32W
amp Lumens:	2,400		
fficacy:	75 LPW		

Technical Specifications

Listings

UL Listing:

Suitable for wet locations

Electrical

Emergency Battery Backup:

Bodine "Coldpak" will operate the CFL lamp fo 90 minutes if power fails. Rated -20°C to +55°C. Battery is a maintenance free NiCad with 7 - 10 year life. Wired for 277V.

Sockets:

Porcelain with all copper current carrying components.

Socket:

Glazed porcelain 4kv pulse rated with nickel plated screw shell and spring contacts.

Quad Tap:

Fixture works with 120, 208, 240 and 277 Volts.

Construction

Housing:

Precision die cast aluminum, 1/2" NPS threaded arm with locking swivel fits all standard mounting boxes.

Reflector:

Anodized semi-specular aluminum.

Lens:

Thermal tempered shock resistant glass.

Lens Gasket:

High temperature tubular silicone set in die cast retaining groove remains in place during relamping.

Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

Ballast Minimum Starting Temperature:

0 Deg F.

Other

Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

Patents:

Pat. D420,458.

Features

Easy clip for tool-less relamping with Vandal proof screw capability

Integra hood glare shield for friendly lighting when properly aimed

Silicone gasket stays in place for durable weatherproofing & easy relamping

Precision die cast aluminum housing with durable polyester powder coating

Variable beam spread with 2 position adjustable socket

Long life lamp included

Mounting arm with sturdy locking teeth & internal gasket