



Color: White

Technical Specifications

Listings

UL Listing:

Suitable for wet locations. Suitable for ground mounting

Construction

Housing:

Precision die cast aluminum. 1/2" NPS locking Swivel Arm, Wall Bracket Trunnion or Slip Fitter.

Reflector:

Anodized aluminum. Field adjustable beam spread. Rotates 90° for horizontal or vertical lamp position.

Lens Frame & Glare Shield:

Precision die cast aluminum. Hinged for easy access. Phillips head screws for added security.

Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

Lens:

Thermal tempered shock resistant glass, 3/16" thick.

Features

Integra hood glare shield for friendly lighting when properly aimed

Silicone gasket for durable weatherproofing & easy relamping

Precision die cast aluminum housing and lens frame with durable polyester powder coating

Anodized aluminum reflector rotates for horizontal or vertical lamp position

Medium base 4kv pulse rated socket

Two field adjustable socket positions allow fine tuning of beam spread)

Fins for heat dissipation extend lamp and ballast life

Prepared By: Date:	Project:	Туре:
	Prepared By:	Date:

Lamp Info		Ballast Info	
Туре:	Triple 64W	Туре:	Electronic QT
Watts:	64W	120V:	0.6A
Shape/Size:	N/A	208V:	0.5A
Base:	N/A	240V:	0.4A
ANSI:	N/A	277V:	0.3A
Hours:	12,000	Input Watts:	72W
Lamp Lumens:	4,800	Efficiency:	89%
Efficacy:	67 LPW		

Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act

Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

Lens Gasket:

Ground Mounting:

Ground Mounting:

for sturdy installation.

Maximum EPA 1.1

CFL Plug in type, GX24q-4 base.

Electrical

Socket:

Other

Patents:

Pat. D544,125.

cap for sturdy installation.

relamping.

EPA:

High temperature one piece molded silicone set in die

Use the new MPM19 PVC Mighty Post with aluminum

Use the new MPM19 Mighty Post with aluminum cap

cast retaining groove. Remains in place during