Project: Type: Prepared By: Date:



UPC: 01.93E+11











Features and Benefits

Replacement for conventional decorative lamps

Filament LED construction gives a unique traditional look and feel for decorative and ambient applications

Produces rich and vibrant colors, >90CRI

Traditional glass envelop

Rated for use in enclosed and open fixtures in wet locations

Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs

Title 20 Compliant, ENERGY STAR Compliant, UL Listed

Smooth uniform dimming down to 10% (check dimmer compatibility list)

Technical Specifications

Performance

Product Type:

Decorative

Input Wattage:

3W

Lumens (Nominal):

350

Color Accuracy:

90 CRI

Color Temperature:

3000K

Dimmable:

Yes, down to 10%

L70 Lifespan:

15,000-Hour LED lifespan based on IES LM-70 results

Construction

Bulb Shape:

G25

Enclosure Material:

Glass

Housing Finish:

Clear

Base Type:

E26

Beam Angle:

360°

Electrical

Power Factor:

>0.7

Input Voltage:

120V

Operating Frequency:

60 Hz

Operating Temperature:

-20°C - 40°C

Other

Equivalency:

40W

Technical Specifications (continued)

Other

Technology EQ:

Incandescent

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

Safety Listing:

UL Listed

Environment/Fixture Rating:

Wet / Enclosed

ENERGY STAR V2.0:

This product is ENERGY STAR® Version 2.0 Certified

Energy Star ID:

2366766

T20 Compliant:

Yes, Title 20 Tier 2

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Model Number:

G25-3-E26-930-F-C

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
10.3 x 6.9 x 5.7	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	6	0	0	0
PALLET	528	0	0	0

Dimension

