HID-120-EX39-840-BYP-PT



Replace 50 - 600W metal halide lamps with an EX39 base for Post Tops in enclosed or open fixtures. 50,000-hour lifespan. Use 76% less energy than MH.

Color: White Weight: 3.5 lbs

Project:	Туре:
Prepared By:	Date:

Driver Info

LED Info

Watts 120.00W
Color Temp 4000K (Cool

4000K (Cool Power Factor >0.9 White) Flicker <309

Lumens 18,000 Efficacy 150 LPW Flicker <30% THDi N/A

Input Voltage 100-277V

Color Accuracy 80 CRI

L70 Accuracy 50,000

Technical Specifications

Technical Specifications

Product Type:

HID

Bulb Shape:

Post Top

Wattage: 120W

Wattage Equivalency:

600W HID

Typical Lumen Output:

18000

Efficacy:

150 lm/W

Color Temperature: 4000K Cool White

CRI:

80

Base Type:

EX39

L70 Lifespan:

50,000 hours

Operating Temperature:

-30°C - 60°C

Dimmable:

No

Beam Angle:

360°

Warranty:

5-Year, No-Compromise Warranty

Installation Type:

Type B, Ballast Bypass

Installation Orientation:

For Vertical Installation Only

For Use in Emergency Fixtures:

No

For Use Outdoors in Open Fixtures:

No

Electrical Characteristics

Input Voltage:

100-277V

HID-120-EX39-840-BYP-PT



Technical Specifications (continued)

Electrical Characteristics Flicker: UL Classified:

Power Factor: <30% Yes

>0.9 THDi: DLC Product Code:
Operating Frequency: <20% PLSTU1M72Z3Z
50 / 60 Hz Listings CEC Status:

Input Current @ 120V: UL Listed: Lawful for sale in California

1mA Yes