## HID-120-EX39-850-BYP-PT



Replace 50 - 600W metal halide lamps with an EX39 base for Post Tops in enclosed or open fixtures. 50,000-hour lifespan. Use 76% less energy than MH.

Color: White Weight: 3.5 lbs

Project:	Туре:
Prepared By:	Date:

Driver Info LED Info

 Watts
 120.00W
 Input Voltage
 100-277V

 Color Temp
 5000K (Daylight)
 Power Factor >0.9

 Lumens
 18,000
 Flicker
 <30%</td>

 Efficacy
 150 LPW
 THDi
 N/A

Color Accuracy 80 CRI R9

L70 Accuracy 50,000

## **Technical Specifications**

**Technical Specifications** 

**Product Type:** 

HID

**Bulb Shape:** 

Post Top

Wattage:

wanage

120W

Wattage Equivalency:

600W HID

**Typical Lumen Output:** 

18000

Efficacy:

150 lm/W

**Color Temperature:** 

5000K Daylight

CRI:

80

Base Type:

EX39

L70 Lifespan:

50,000 hours

Operating Temperature:

-30°C - 60°C

Dimmable:

No

Beam Angle:

360°

Warranty:

5-Year, No-Compromise Warranty

Installation Type:

Type B, Ballast Bypass

Installation Orientation:

For Vertical Installation Only

For Use in Emergency Fixtures:

No

For Use Outdoors in Open Fixtures:

No

**Electrical Characteristics** 

Input Voltage:

100-277V

## HID-120-EX39-850-BYP-PT



**Technical Specifications (continued)** 

Electrical Characteristics Flicker: UL Classified:

Power Factor: <30% Yes

>0.9 THDi: DLC Product Code:
Operating Frequency: <20% PLU4ULZ0J905
50 / 60 Hz Listings CEC Status:

Input Current @ 120V: UL Listed: Lawful for sale in California

1mA Yes