HID-45-EX39-840-BYP-PT

| Replace 50 - 400W MH lamps for post tops, low bays, and high bays, in enclosed or open fixtures. 50,000-hour lifespan. Use 76% less energy than MH. |
|---|

Color: White

Weight: 1.6 lbs


Technical Specifications

| Listings | Bulb Type: | LED Characteristics |
|--|--|---|
| UL Listed: | Post Top | Lifespan: |
| Yes | Base Type: | 50,000-hour LED lifespan based on IES LM-70 results |
| UL Classified: | EX39, Mogul Base | Other |
| Yes | Dimmable: | Equivalent: |
| FCC: | No | 175W HID Post Top |
| Yes | Construction | Warranty: |
| Rohs: | Operating Temperature: | 5 years |
| Yes | -20 - 40°C | Optical |
| CEC Status: | Bare Lamp Illuminated Length (inches): | Beam Angle: |
| awful for sale in California | 5.12" | 360° |
| DLC Qualified: | MOL (inches): | Shipping Information |
| Yes | 9.57" | Case Qty: |
| DLC Listed: | MOD (inches): | 12 |
| This product is on the Design Lights Consortium (DLC) | 3.35" | Case Dimensions: |
| Qualified Products List and is eligible for rebates from DLC Member Utilities. | Minimum Compartment Size (inches): | 15.55 x 11.81 x 11.42 |
| LC Product Code: P67182DU | Length: 7.99" | Pallet Quantity of Pieces: |
| Description | Width: 7.99" Height: 11.02" | 216 |
| Lamp Type: | | Pallet Dimensions: |
| HID | | 37.4 x 33.07 x 38.98 |

| Project: | | Туре: | |
|----------------|---------------|--------------------|----------|
| Prepared | Ву: | Date: | |
| Driver Info | | LED Info | |
| Watts: | 45W | Input Voltage: | 100-277V |
| Color Temp: | 4000K (Cool W | hite)Power Factor: | 0.9 |
| Lumens: | 6,800 | Flicker: | <30% |
| Efficacy: | 151 LPW | THDi: | <20% |
| Color Accuracy | /: 80 CRI | | |
| L70 Accuracy: | 50,000 | | |

Need help? Tech help line: (888) RAB-1000 Email: sales@rablighting.com Website: www.rablighting.com Copyright © 2018 RAB Lighting Inc. All Rights Reserved Note: Specifications are subject to change at any time without notice

HID-45-EX39-840-BYP-PT



Features

Replacement for Conventional HID Lamps

Water and dust resistant - ideal for outdoor fixtures

Thermal technology extends LED lifetime

Integrated Heat Sink Quickly Dissipates Heat without onboard fan

Internal Driver, Eliminates the Need for External Driver or Ballast

Includes 4kV Surge Protection

Instantly powers on without warm up time