# HID-63-EX39-840-BYP-PT

| Project: | Type: |
|---|---|
| **Prepared By:** | **Date:** |

### Driver Info

| | |
|---|---|
| Watts: | 63W |
| Color Temp: | 4000K (Cool White) |
| Lumens: | 9,500 |
| Efficacy: | 151 LPW |
| Color Accuracy: | 80 CRI |
| L70 Accuracy: | 50,000 |

### LED Info

| | |
|---|---|
| Input Voltage: | 100-277V |
| Power Factor: | 0.9 |
| Flicker: | <30% |
| THDi: | <20% |

Replace 50 - 400W MH lamps for post tops, low bays, and high bays, in enclosed or open fixtures. 50,000-hour lifespan. Use 76% less energy than MH.

Color: White          Weight: 1.8 lbs

## Technical Specifications

### Listings

**UL Listed:**
Yes

**UL Classified:**
Yes

**FCC:**
Yes

**Rohs:**
Yes

**CEC Status:**
Lawful for sale in California

**DLC Qualified:**
Yes

**DLC Listed:**
This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.
DLC Product Code: PPW890PY

### Description

**Lamp Type:**
HID

**Bulb Type:**
Post Top

**Base Type:**
EX39, Mogul Base

**Dimmable:**
No

### Construction

**Operating Temperature:**
-20 - 40°C

**Bare Lamp Illuminated Length (inches):**
5.71"

**MOL (inches):**
10.16"

**MOD (inches):**
3.35"

**Minimum Compartment Size (inches):**
Length: 7.87"
Width: 7.87"
Height: 10.62"

### LED Characteristics

**Lifespan:**
50,000-hour LED lifespan based on IES LM-70 results

### Other

**Equivalent:**
250W HID Post Top

**Warranty:**
5 years

### Optical

**Beam Angle:**
360°

### Shipping Information

**Case Qty:**
12

**Case Dimensions:**
15.55 x 11.81 x 12.01

**Pallet Quantity of Pieces:**
216

**Pallet Dimensions:**
37.4 x 33.07 x 38.98

# HID-63-EX39-840-BYP-PT

## Dimensions



5 11/16"
145mm

10 3/16"
258mm

3 3/8"
85mm

## Features

Replacement for Conventional HID Lamps

Water and dust resistant - ideal for outdoor fixtures

Thermal technology extends LED lifetime

Integrated Heat Sink Quickly Dissipates Heat without onboard fan

Internal Driver, Eliminates the Need for External Driver or Ballast

Includes 4kV Surge Protection

Instantly powers on without warm up time

Need help? Tech help line: **(888) RAB-1000** Email: **sales@rablighting.com** Website: **www.rablighting.com**

Copyright © 2018 RAB Lighting Inc. All Rights Reserved    Note: Specifications are subject to change at any time without notice

Page 2 of 2