



Dimensions



Features

- 0-10V Dimming, standard
- 100,000-Hour LED lifespan

Ordering Matrix

| Family       | Distribution  | Lumen Output | Mounting            | CRI/CCT            | Finish                   | Voltage/Driver           | Sensor Options             | Lightcloud Option           |                             |                 |                 |                   |                   |                   |            |           |                  |           |                            |                             |                    |                            |                              |                              |                         |                       |                             |
|--------------|---------------|--------------|---------------------|--------------------|--------------------------|--------------------------|----------------------------|-----------------------------|-----------------------------|-----------------|-----------------|-------------------|-------------------|-------------------|------------|-----------|------------------|-----------|----------------------------|-----------------------------|--------------------|----------------------------|------------------------------|------------------------------|-------------------------|-----------------------|-----------------------------|
| IVA          | T4            | 45L          | PA                  | 730                | W                        | U                        | ^                          | ^                           |                             |                 |                 |                   |                   |                   |            |           |                  |           |                            |                             |                    |                            |                              |                              |                         |                       |                             |
| T2 = Type II | T3 = Type III | T4 = Type IV | T5S = Type V Square | FT = Forward Throw | 45L = 4,500 lumens (38W) | 75L = 7,500 lumens (67W) | 100L = 10,000 lumens (94W) | 130L = 13,000 lumens (117W) | PA = Universal Pole Adapter | WM = Wall mount | SF = Slipfitter | 750 = 70CRI 5000K | 740 = 70CRI 4000K | 730 = 70CRI 3000K | Z = Bronze | W = White | G = Roadway Gray | K = Black | U = 120-277V 0-10V Dimming | H = 347-480V, 0-10V Dimming | Blank = No Options | /WS = 8ft lens Wattstopper | /WS2 = 20ft lens Wattstopper | /WS4 = 40ft lens Wattstopper | /7PR = 7-pin receptacle | Blank = No Lightcloud | /LC = Lightcloud Controller |