



The Gateway is the brain of Lightcloud. It communicates with RAB's servers via private 3G cellular connection, so no internet access is required. Plus, it features an uninterruptible power supply for added peace of mind.

Color: Black

Weight: 0.9 lbs

Project:	Type:
Prepared By:	Date:

Technical Specifications

Listings

UL Listing:

Indoor use only.

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.

Electrical

Input Voltage:

120-277 VAC

Frequencies:

50/60 Hz

Current Draw:

70 mA @ 120VAC

43 mA @ 277VAC

Battery Backup:

Rechargeable Lithium Ion

Construction

Operating Temperature Range:

0°C to 40°C

Storage Temperature Range:

-20°C to 60°C

Maximum Relative Humidity:

85%

Wire Gauge:

18 AWG, stranded

Junction Box:


Contains integral junction box for hard-wired installation by a qualified electrician.

Other

Warranty:

10-year full hardware warranty with 100% repair/replacement coverage for all properly installed devices.

Dimensions



Features

- Connects with up to 200 Lightcloud devices
- Communicates with Lightcloud devices via 2.4 GHz wireless mesh network
- User-serviceable, built-in UPS battery backup (lasts approximately 2 hours)
- Cloud-based management - no software to install or maintain
- Connects to Lightcloud service using secure cellular 3G connection and no internet access is required
- Easy setup - simply power on, confirm a cellular signal and call 844-LIGHTCLOUD
- To activate, go to lightcloud.com/activate
- Warranty is active as long as service plan is active