PLT-15.5-H-835-BYP

| Project: | Туре: | Prepared By: | Date: |
|---------------|-------------------|---|--|
| | | Ballast Bypass. line voltage wit Compatible wit 50,000 hour Lif Environmentall UL Classified, D Rated for use in locations Non-Dimmable | y friendly, no mercury used DLC Listed n enclosed and open fixtures in dry or damp |
| c Ru s | UPC: 019813918235 | ROHS COMPLIANT | |
| Technical Spe | ecifications | | Base Type: |
| Product Type: | Non-Dim | - | 2-Pin G24d |

| Product Type: | Non-Dim | 2-Pin G24d |
|--------------------|---|------------------------------|
| Compact | L70 Lifespan: | Beam Angle: |
| Input Wattage: | 50,000-Hour LED lifespan based on IES LM-80 | 110° |
| 15.5W | results and TM-21 calculations | Electrical |
| Lumens (Nominal): | Construction | THD: 20% Power Factor: |
| 1900 | Bulb Shape: | |
| Efficacy: | PLT-H | |
| 123 lm/W | Enclosure Material: | >0.9 |
| Color Accuracy: | Polycarbonate | Input Voltage: |
| 80 | Housing Finish: | 120-277V |
| Color Temperature: | White | |
| 3500K | Lens Finish: | |
| | Frosted | |



RAB

Technical Specifications (continued) Electrical Technology EQ: RoHS: CFL Mercury and UV free. RoHS-compliant **Operating Frequency:** components. Warranty (Years): 50 / 60 Hz FCC: RAB warrants that our LED products will be free **Operating Temperature:** from defects in materials and workmanship for a Complies with Part 15 of the FCC Rules -20°C - 45°C period of five (5) years from the date of delivery Model Number: Installation to the end user, including coverage of light T10221(PLT-15.5-H-835-BYP) output, color stability, driver performance and Installation Method: fixture finish. RAB's warranty is subject to all terms and conditions found at UL Type B, Ballast Bypass rablighting.com/warranty. **Burning Position:** Horizontal Compliance Other Safety Listing: **Equivalency:** UL Classified, UL Recognized 42W G24d/G24q/Gx24q **Environment/Fixture Rating:** Damp / Open


Minimum Compartment Size

| Length x Width x Height [in] | Lamp Quantity | |
|------------------------------|---------------|--|
| 7 x 7.8 x 6.1 | 1 | |


Case and Pallet Dimensions

| | QTY | LENGTH (in) | WIDTH (in) | HEIGHT (in) |
|--------|-----|-------------|------------|-------------|
| CASE | 12 | 0 | 0 | 0 |
| PALLET | 440 | 0 | 0 | 0 |

Dimension



PLT-15.5-H-835-BYP



RAB