PS30-36-EX39-830-ND 120-277V

Project:	Туре:	Prepared By: Date:	
		Features and Benefits Replacement for High output incandescent or Metal Ha	lide and
		High Pressure Sodium HID Lamps Commercial Grade	
		Large metal heatsink for optimal heat dissipation	
		In HID retrofit applications - Integral Driver enables lan wired directly to line voltage. Must bypass ballast.	ip to be
		Rated for use in enclosed and open fixtures in dry or da locations	amp
	RAB	Ideal for post top, bollards, and outdoor corridor lightin	g
	F II J	50,000 hour Lifespan	
		Environmentally friendly, no mercury used	
		UL Listed, DLC Listed	
		Non-Dimmable	
	UPC: 01.93E+11	Universal Voltage 120V through 277V	
LISTED	FC	5 Year No Compromise Warranty	

Technical Specifications

Performance	L70 Lifespan:	Beam Angle:	
Product Type:	50,000-Hour LED lifespan based on IES LM-70	230°	
Commercial Bulb	results	Electrical	
Input Wattage:	Construction	THD:	
36W	Bulb Shape:	<20%	
Lumens (Nominal):	Construction	Power Factor:	
4900	Enclosure Material:	>0.9	
Color Accuracy:	Die Cast Aluminum	Input Voltage:	
82 CRI	Housing Finish:	120-277V	
Color Temperature:	White	Operating Frequency:	
3000K	Lens Finish:	60 Hz	
Dimmable:	Frosted		
Non-Dim	Base Type:		
	EX39		

RAB

Technical Specifications (continued)

Electrical

Operating Temperature:

-20°C - 45°C

Installation

Installation Method:

If replacing HID Lamps must bypas the ballast

Other

Equivalency:

175W

Technology EQ:

Metal Halide or High Pressure Sodium

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty.</u>

Compliance

Safety Listing:

UL Listed

Environment/Fixture Rating:

Damp / Enclosed

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Model Number:

P10023(PS30-36-EX39-830-ND 120-277V)

mum Compartment Size				
Length x Width x Height [in]	Lamp Quantity			
7.9 x 8.5 x 12	1			

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	1	0	0	0
PALLET	450	0	0	0

