R20-11-E26-830-DIM

Image: State	Project:	Туре:	Prepared By:	Date:
	LISTED	UPC: 0192552013932	Energy efficient replace lamps Constructed from dura Rated for use in enclose Frosted lens produces Longer lifespan comp and maintenance cost ENERGY STAR Complia	ant colors >90CRI eement for incandescent and halogen Reflector able plastic which lowers risk of breakage sed and open fixtures in dry or damp locations smooth diffuse light ared to legacy equivalents minimizes replacemer s ant, Title 20 Compliant

Performance	Dimmable:	Base Type:
Product Type:	Yes	E26
Reflector	Compliance	Enclosure Material:
Input Wattage:	UL Listed:	Plastic
11W	Suitable for damp locations	Beam Angle:
Typical Lumen Output:	Enclosed Fixtures:	110°
940lm	Suitable for use in enclosed fixtures	Electrical
Efficacy:	DLC Model Number:	Power Factor:
85.5 lm/W	R10085(R20-11-E26-830-DIM)	>0.9
CRI:	LED Characteristics	Operating Temperature:
>80	Color Temperature:	-20°C - 40°C
L70 Lifespan:	3000K	
25,000-Hour LED lifespan based on IES LM-70 results	Construction	
	Bulb Shape:	
	R20	

RAB

R20-11-E26-830-DIM

RAB

Technical Specifications (continued)

Electrical

Input Voltage:

120V

Operating Frequency:

60 Hz

Other

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty</u>.

Equivalency:

75W Halogen

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	10.8	7.87	4.2
PALLET	0	0	0	0