RDCANIC6R RAB



Project:	Туре:
Prepared By:	Date:

	LED Info	
N/A	Watts:	OW
N/A	Color Temp:	N/A
N/A	Color Accuracy:	N/A
N/A	L70 Lifespan:	N/A
N/A	Lumens:	N/A
0W	Efficacy:	N/A
N/A		
	N/A N/A N/A N/A OW	N/A Watts: N/A Color Temp: N/A Color Accuracy: N/A L70 Lifespan: N/A Lumens: 0W Efficacy:

Technical Specifications

Listings

UL Listed:

Suitable for wet locations in a covered ceiling

Construction

IC Rating:

Suitable for direct contact with insulation

Housing:

Precision die cast aluminum

Remodeler:

Mounting spring clips for use with 5/8" to 1" sheet rock ceilings

Green Technology:

Mercury and UV-free. RoHS compliant components. Polyester powder coat finish formulated without the use of VOCs or toxic heavy metals.

Finish:

Formulated for high-durability and long lasting color

Other


Warranty:


RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions





RDCANIC6R



Size	Shape
6	R
4 = 4" 6 = 6"	R = Round
	6 4 = 4"