T5HE-6-24G-840-DIR

Project:	Туре:	Prepared By:	Date:
•	UPC: 0	Easy to instal instructions 50,000 hour I Rated for use locations Diffused frost Compatible w check Compa Instant on ful Environmenta NSF Listed: N	in enclosed and open fixtures in dry or damp red lens will maintain the same light quality over time with most program start electronic T5 ballasts, Please tibility List. I brightness ally friendly, no mercury used SF/ANSI Standard 2 - Food Equipment - Splash Zone rt Food Zone without additional fixture considerations
LISTED	NSF F	-C	
ULISTED Technical Specificati Performance			Lens Finish:
Performance	ons		
Performance Product Type:	ons Dimmable		Lens Finish:
Performance Product Type:	ONS Dimmable Yes L70 Lifesp 50,000-Hour	e: Dan: r LED lifespan based on IES LM-80	Lens Finish: Frosted
Performance Product Type: Linear	ONS Dimmable Yes L70 Lifesp 50,000-Hour results and	e: Dan: r LED lifespan based on IES LM-80 TM-21 calculations	Lens Finish: Frosted Base Type:
Performance Product Type: Linear Input Wattage: 6W	ONS Dimmable Yes L70 Lifesp 50,000-Hour results and Construct	e: Pan: r LED lifespan based on IES LM-80 TM-21 calculations tion	Lens Finish: Frosted Base Type: G5
Performance Product Type: Linear Input Wattage: 5W Lumens (Nominal):	ONS Dimmable Yes L70 Lifesp 50,000-Hour results and Construc Length No	e: Pan: r LED lifespan based on IES LM-80 TM-21 calculations tion	Lens Finish: Frosted Base Type: G5 Beam Angle:
Performance Product Type: Linear Input Wattage: 6W Lumens (Nominal): 1000	ONS Dimmable Yes L70 Lifesp 50,000-Hour results and T Construc Length No 2FT	e: Dan: r LED lifespan based on IES LM-80 TM-21 calculations tion Dominal:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160°
Performance Product Type: Linear Input Wattage: 6W Lumens (Nominal): 1000 Efficacy:	ONS Dimmable Yes L70 Lifesp 50,000-Hour results and Construc Length No	e: Dan: r LED lifespan based on IES LM-80 TM-21 calculations tion Dominal:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical
Performance Product Type: Linear Input Wattage: 6W Lumens (Nominal): 1000 Efficacy: 167 lm/W	ONS Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct Length No 2FT Bulb Shap T5	e: Dan: r LED lifespan based on IES LM-80 TM-21 calculations tion pominal: pe:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD:
Performance Product Type: Linear Input Wattage: 6W Lumens (Nominal): 1000 Efficacy: 167 lm/W Color Accuracy:	ONS Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct Length No 2FT Bulb Shap T5 Enclosure	e: Dan: r LED lifespan based on IES LM-80 TM-21 calculations tion pominal: pe:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20%
-	ONS Dimmable Yes L70 Lifesp 50,000-Hour results and Construct Length No 2FT Bulb Shap T5 Enclosure Glass	e: Dan: r LED lifespan based on IES LM-80 TM-21 calculations tion pminal: pe: Material:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20% Power Factor:
Performance Product Type: Linear Input Wattage: 6W Lumens (Nominal): 1000 Efficacy: 167 lm/W Color Accuracy: 80	ONS Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct Length No 2FT Bulb Shap T5 Enclosure	e: Dan: r LED lifespan based on IES LM-80 TM-21 calculations tion pminal: pe: Material:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20% Power Factor:

RAB

Technical Specifications (continued)

Electrical

Operating Temperature:

-20°C-45°C

Input Voltage:

120-277V

Operating Frequency:

50 / 60 Hz

Installation

Installation Method:

UL TYPE A, Plug and Play

Other

Equivalency:

F14T5

Technology EQ:

Fluorescent

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

Safety Listing:

UL Listed

Environment/Fixture Rating:

Damp / Enclosed

NSF Listing:

NSF/ANSI Standard 2 - Food Equipment (noncontact), Splash Zone, and Non-Food Zone. (Not for Direct Food Zone without additional fixture considerations)

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

