# T5HE-9-36G-835-DIR

Project:	Туре:	Prepared By:	Date:
		Easy to inst instructions 50,000 hour Rated for us locations Diffused from Compatible check Comp Instant on fu Environmen NSF Listed:	r Lifespan se in enclosed and open fixtures in dry or damp sted lens will maintain the same light quality over time with most program start electronic T5 ballasts, Please batibility List. ull brightness stally friendly, no mercury used NSF/ANSI Standard 2 - Food Equipment - Splash Zone ect Food Zone without additional fixture considerations
LISTED	NSF.	C	ILC LISTED
-	INSE F	÷C	
Performance	Dimmable	÷C	Lens Finish:
Performance Product Type:	Dins Pins Pins Pins Pins Pins Pins Pins		<b>Lens Finish:</b> Frosted
Performance Product Type: Linear Input Wattage:	Dins Dimmable Yes L70 Lifesp 50,000-Hour		<b>Lens Finish:</b> Frosted <b>Base Type:</b> G5
Performance Product Type: Linear Input Wattage: 9W	Dins Dimmable Yes L70 Lifesp 50,000-Hour	an: LED lifespan based on IES LM-80 M-21 calculations	Lens Finish: Frosted Base Type: G5 Beam Angle:
Performance Product Type: Linear Input Wattage: DW Lumens (Nominal):	Dins Dimmable Yes L70 Lifesp 50,000-Hour results and T	an: LED lifespan based on IES LM-80 M-21 calculations tion	Lens Finish: Frosted Base Type: G5 Beam Angle: 160°
Performance Product Type: Linear Input Wattage: 9W Lumens (Nominal): 1300	Dons Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct	an: LED lifespan based on IES LM-80 M-21 calculations tion	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical
Performance Product Type: Linear Input Wattage: 9W Lumens (Nominal): 1300 Efficacy:	Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct Length No	an: LED lifespan based on IES LM-80 M-21 calculations tion minal:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD:
Performance Product Type: Linear Input Wattage: 9W Lumens (Nominal): 1300 Efficacy: 144 lm/W	Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct Length No 3FT	an: LED lifespan based on IES LM-80 M-21 calculations tion minal:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20%
Performance Product Type: Linear Input Wattage: 9W Lumens (Nominal): 1300 Efficacy: 144 lm/W Color Accuracy:	DINSE DIMMABLE Yes L70 Lifesp 50,000-Hour results and T Construct Length No 3FT Bulb Shap	C an: LED lifespan based on IES LM-80 M-21 calculations tion minal: e:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20% Power Factor:
Performance Product Type: Linear Input Wattage: 9W Lumens (Nominal): 1300 Efficacy: 144 lm/W Color Accuracy: 80	Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct Length No 3FT Bulb Shap T5	C an: LED lifespan based on IES LM-80 M-21 calculations tion minal: e:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20%
University of the second secon	DINSE DIMMABLE Yes L70 Lifesp 50,000-Hour results and T Construct Length No 3FT Bulb Shap T5 Enclosure	C C C C C C C C C C C C C C C C C C C	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20% Power Factor:

RAB

# **Technical Specifications (continued)**

### **Electrical**

**Operating Temperature:** 

-20°C-45°C

Input Voltage:

120-277V

Operating Frequency:

50 / 60 Hz

## Installation

Installation Method:

UL TYPE A, Plug and Play

#### Other

Equivalency:

F21T5

## Technology EQ:

Fluorescent

## Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

### Compliance

Safety Listing:

UL Listed

## **Environment/Fixture Rating:**

Damp / Enclosed

#### **NSF Listing:**

NSF/ANSI Standard 2 - Food Equipment (noncontact), Splash Zone, and Non-Food Zone. (Not for Direct Food Zone without additional fixture considerations)

## **RoHS:**

Mercury and UV free. RoHS-compliant components.

## FCC:

Complies with Part 15 of the FCC Rules

