

<b>Project:</b>	<b>Type:</b>	<b>Prepared By:</b>	<b>Date:</b>
-----------------	--------------	---------------------	--------------



UPC: 0192552005272



### Features and Benefits

- Impact resistant, can handle demanding construction site environments
- Omni-directional light distribution
- Lightweight design with high output
- US Cord and Plug, linkable up to 6 units
- IP64 Water and Dust resistant
- 6kV surge protection built in
- 50,000 hour Lifespan
- 120V
- Meets OSHA Compliance Standard 1915.82(b) for Temporary Lighting: 30-foot spacing for minimum of 5 foot candles
- 5 Year No Compromise Warranty

### Technical Specifications

#### Performance

**Product Type:**

HID

**Input Wattage:**

60W

**Typical Lumen Output:**

7200lm

**Efficacy:**

120 lm/W

**CRI:**

>80

**L70 Lifespan:**

50,000-Hour LED lifespan based on IES LM-70 results

**Dimmable:**

Yes

**Compliance**

**UL Listed:**

Suitable for damp locations

**Enclosed Fixtures:**

Suitable for use in enclosed fixtures

**DLC Model Number:**

H10076(TEMP-60-850/15CP)

**LED Characteristics**

**Color Temperature:**

5000K

**Construction**

**Bulb Shape:**

Work light

**Base Type:**

Plug

**Endcap Material:**

Metal

**Enclosure Material:**

Polycarbonate

**Beam Angle:**

360°

**Electrical**

**Power Factor:**

>0.9

## Technical Specifications (continued)

### Electrical

**Operating Temperature:**

-30°C - 60°C

**Input Voltage:**

120V

**Operating Frequency:**

60 Hz

### Electrical Characteristics

**THD:**

<20%

**Flicker:**

<30%

### Installation

**Installation Orientation:**

Vertical

### Other

**Warranty (Years):**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

## Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	4	20.5	11.4	20.5
PALLET	24	40.9	42.9	48

## Dimension

