## **VXBR100P/F13**





Die cast aluminum construction. Wall bracket plus junction box with sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes. Lamp supplied.

Color: Natural Weight: 28.0 lbs

| Project:     | Туре: |
|--------------|-------|
| Prepared By: | Date: |

| Lamp Info    |          | Ballast Info |          |
|--------------|----------|--------------|----------|
| Type:        | 13W Quad | Type:        | NPF 120V |
| Watts:       | 13W      | 120V:        | 0.35A    |
| Shape/Size:  | N/A      | 208V:        | N/A      |
| Base:        | N/A      | 240V:        | N/A      |
| ANSI:        | N/A      | 277V:        | N/A      |
| Hours:       | 10,000   | Input Watts: | 17W      |
| Lamp Lumens: | 825      | Efficiency:  | 76%      |
| Efficacy:    | 49 LPW   |              |          |
|              |          |              |          |

## **Technical Specifications**

#### Listings

#### **UL Listing:**

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90°C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

#### **Electrical**

#### Wattage:

See catalog number chart for maximum wattage with clear glass, colored glass and Permaglobes.

#### Socket:

Premium porcelain with 150°C 8" leads attached. Fastened with 2 stainless steel screws.

## Construction

#### Globes:

Supplied with clear heat resistant glass globes unless otherwise stated. Colored and white glass globes available. Unbreakable RAB Permaglobes available in clear and in color.

#### **Optional Reflectors:**

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See RV series.

#### Globe:

Supplied with clear flat bottom prismatic polycarbonate globe. Not for use with diecast or wire guard.

#### **Optional Guard:**

Order flat bottom guard separately. CAT# GD100BAR.

#### **Ballast Minimum Starting Temperature:**

32°F

#### Optical

#### F13:

Compact Fluorescent 13W.

#### Other

#### **Country of Origin:**

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

#### **Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act

#### Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

## Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

## GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

# **VXBR100P/F13**



## Features

Set screw keeps guard securely in place

Junction box with sturdy mounting lugs

All stainless steel hardware

Close-up plugs allow Phillips or slotted screwdrivers for easy installation

High temperature silicone internal gaskets

Premium porcelain socket with 150C 8" long leads attached

Clear heat resistant glass globes standard Polycarbonate Permaglobes available