# WP2CH70QTW/PC





Wallpack with cutoff glare shield. All aluminum precision die cast construction with tempered glass lens.  $30^{\circ}$ . cutoff strip included. Lamp supplied.

Color: White

## Technical Specifications

#### Electrical

#### Photocell:

120V Button Photocell Included. Photocell is only compatible with 120V.

#### Quad Tap:

Fixture works with 120, 208, 240, and 277 volts.

#### Listings

#### **UL Listing:**

Suitable for wet locations. HID fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from ballast.

#### EISA 2007 Compliant:

This product complies with the new law for metal halide ballast efficiency. This law goes into effect January 1st, 2008. Pulse Start offers Longer Lamp Life, Faster Startup and Faster Restrike.

#### Construction

Housing:

Die cast aluminum, 1/2" NPS tapped holes top, both sides and back for conduit or photocontrol. Hinged refractor frame. Continuous silicone rubber gasket.

#### **Reflector:**

Weight: 14.0 lbs

Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

#### **Cutoff Lens:**

Tempered glass.

#### Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

## Optical

#### **Refractor:**

Prismatic optics designed to minimize glare and throw light down and out. Heat resistant borosilicate glass.

## Other

#### **Country of Origin:**

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

| Project:                  |                 | Туре:        |           |
|---------------------------|-----------------|--------------|-----------|
| Prepared By:              |                 | Date:        |           |
| Lamp Info                 |                 | Ballast Info |           |
| Туре:                     | ED17            | Туре:        | HX-HPF QT |
| Watts:                    | 70W             | 120V:        | .7/.8A    |
| Shape/Size:               | N/A             | 208V:        | N/A       |
| Base:                     | N/A             | 240V:        | N/A       |
| ANSI:                     | N/A             | 277V:        | N/A       |
| Hours:                    | 15,000          | Input Watts: | 90W       |
| Lamp Lumens:<br>Efficacy: | 5,600<br>62 LPW | Efficiency:  | 78%       |

#### **Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

#### **Recovery Act (ARRA) Compliant:**

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

#### Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

#### **GSA Schedule:**

Suitable in accordance with FAR Subpart 25.4.

# WP2CH70QTW/PC





Precision die cast aluminum housing with durable polyester powder coating

Tempered Glass Refractor and Tempered Glass Lens

Drilling template for easy box mounting

Silicone gasket remains in place during relamping

Top, side and back conduit openings

Cutoff Glare Shield for Friendly Lighting

Long life lamp included

