WP2FCF32/E1





Technical Specifications

Electrical

Emergency Battery Backup:

Bodine "Coldpak" will operate the CFL lamp for 90 minutes if power fails. Rated -20°C to 55°C. Battery is a maintenance free NiCad with 7 - 10 year life. Wired for 120V.

Listings

UL Listing:

Suitable for wet locations. HID fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from ballast.

Construction

Housing:

Die cast aluminum, 1/2" NPS tapped holes top, both sides and back for conduit or photocontrol. Hinged refractor frame. Continuous silicone rubber gasket.

Reflector:

Dimensions

Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

68.4

28

Cutoff Lens:

Tempered glass.

Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

Hours:

Efficacy:

Lamp Lumens:

Optical Refractor:

Prismatic optics designed to minimize glare and throw light down and out. Heat resistant borosilicate glass.

Other

Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

Project:		Туре:	
Prepared By:		Date:	
Lamp Info		Ballast Info	
Туре:	32w Triple	Туре:	Elec HPF QT
Watts:	32W	120V:	0.31A
Shape/Size:	N/A	208V:	N/A
Base:	N/A	240V:	N/A
ANSI:	N/A	277V:	N/A

12,000

2,400

75 LPW

Buy American Act Compliant:

Input Watts:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

32W

Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

Features

Emergency battery backup meets NEC requirement

Test button for required maintenance checks

- Indicator light illuminates when charging
- Maintenance free NiCad battery has 7-10 year life

Hinged door frame opens and remains captive for easy relamping

Silicone gasket remains in place during relamping

Long life lamp included

- 147 3345.cm -