## WPLED26MS

26W

5000K

70 CRI

100000

90 LPW

2,662



LED 26W Wallpacks. Patent Pending thermal management system. 100,000 hour L70 lifespan. 5 Year Warranty.

Color: Bronze

### **Technical Specifications**

#### **LED Characteristics**

#### Lifespan:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

#### **Color Consistency:**

7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

#### Construction

#### **IP Rating:**

Ingress Protection rating of IP66 for dust and water.

## Other

#### Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

#### **Buy American Act Compliant:**

Weight: 8.0 lbs

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

**Project:** 

**Driver Info** 

Type:

120V:

208V:

240V:

277V:

Input Watts:

Efficiency:

**Prepared By:** 

#### **Recovery Act (ARRA) Compliant:**

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

#### **Trade Agreements Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

#### **GSA Schedule:**

Suitable in accordance with FAR Subpart 25.4.

#### Optical

Constant Current

0.26A

N/A

N/A

N/A

30W

88%

**BUG Rating:** 

B1 U0 G0

## **BUG Rating:**

B1 U0 G0

#### Listings

**DLC Listed:** 

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. DLC Product Code: P0000170I

Type:

Date:

LED Info

Color Temp:

Color Accuracy:

L70 Lifespan:

Lumens:

Efficacy:

Watts:

Features

High performance LED light engine

Maintains 70% of initial lumens at 100,000 hours

Weatherproof high temperature silicone gaskets

Superior heat sinking with die cast aluminum housing and external fins

100 up to 277 Volts

5-year warranty

# WPLED26MS



rdering Matrix						
Family	Watts	Color Temp	Sensor	Finish	Photocell	Dimming
WPLED						
	<b>26</b> = 26W	Blank = 5000K (Cool) Y = 3000K (Warm) N = 4000K (Neutral)	Blank = No Sensor MS = Mini Sensor	Blank = Bronze W = White	Blank = No Photocell /PC = 120V Button /PCS = 120V Swivel	Blank = No Dimmin /D10 = Dimmable
					/PC2 = 277V Button	